FOX Knives

Oreste Frati S.r.l. Via La Mola, 4

33085 Maniago - Italy ph. +39 0427 71814 / +39 0427 730376

fax +39 0427 700514 e-mail: info@foxcutlery.com \_\_\_\_NATO N/CAGE CODE: AG180



## 

cod. OMG-1

Blade Steel: N690Co stainless steel

Hardness: HRC 58-60

**Blade Coating:** Physical Vapor Deposition Gun Met **Handle:** black FRN® and 420 stainless steel hammer

Blade Length: 14 cm - 5.51" Overall Length: 26 cm - 10.24" Blade Thickness: 6 mm - 0.24" Weight: 300 gr - 10.58 oz

## Info

The sheath can be attached to a respirator using the integrated MOLLE system.

The KAIMANO is one of the best diving/combat knives in use today.

FOX O.M.G. KAIMANO Italian Navy Special Operation Unit Combat/Diving knife KAIMANO is the exclusivity model of Italian Navy Special Operation Unit, it has built following their strict specification.

The knife develop with O.M.G. company that is one of the leading suppliers in Italy of diving material for the military, has been tested very strictly in several conditions, it has been kept for more than one month inside sea water to can test corrosion and at the end has been selected like the official knife. All the feature of the blade has been studied from the Unit, we have followed their request for production of the knife and of the sheath that is applied in their respirators using MOLLE system place on the back side of the sheath. One of the best diving/combat knife actually used in the field.

## Blade Coating: Physical Vapor Deposition Gun Met

(Physical Vapor Deposition) is a variety of vacuum deposition methods used to deposit thin films by the condensation of a vaporized form of the desired film material onto various workpiece surface. The coating method involves purely physical process such as high temperature vacuum evaporation with subsequent condensation.

Blade Steel: N690Co stainless steel

Acciaio CarbonioCromoCobaltoAzotoManganese Molibdeno NichelFosforoSilicioZolfo TungstenoVaSteelCarbonChromiumCobaltNitrogen Manganese MolybdenuNickel PhosphorousSilicon SulfurTungsVanN690CO 1.0817.301.50-0.401.10--0.40--0.10